

Lean Shelf Wagon



Product description

The Lean Shelf Wagon has been designed to carry SLC's and component trays widely used within the automotive industry. It is designed to be compatible with both your milkrun and automated systems.

For optimised external transport and warehousing the Lean dolly can be used together with the Lean adaptor pallet.

Benefits

- Improve work flow
- Reduce handling costs
- Enable reduction of stock level
- Reduce need for floor space
- Improve ergonomics
- Fast and safe truck loading
- Optimize vehicle fill





Lean Shelf Wagon

Lean Shelf Wagon

External dimensions 806 x 1260 x 1680 mm
 Tare weight (with 2 or 3 shelves) 108-120 kg
 Wheel size 160 mm wheels
 Wheel type 2 fixed & 2 swivel
 Wheel material PU
 Working capacity
 Shelf 150 kg
 Shelf if above 1,2m 100 kg
 Total unit 450 kg


K.Hartwall wheels are equipped with high quality ball bearings and hub caps for high performance and wheel protection.

Surface treatment: Blue zinc plated acc. to EN-ISO2081


Can be towed with all other towable dollies



Standard wheels



ESD hard plastic wheel and non-marking ESD hard plastic wheel



Polyurethane wheel or polyurethane ESD wheel

Designed to carry SLC's

- 4 stack of 600 x 400 mm
- 8 stacks of 300 x 400 mm

Accessories

- Integrated strapping
- Number of shelves (1-4)
- Towing device

Options

- Total brake on 1 or 2 swivel wheels
- RFID compatibility