

Lean Pallet Size Dolly



Product description

The Lean Dolly has been designed to carry pallets, cages, boxes and SLC's widely used within the automotive industry. It is designed to be compatible with both your milkrun and automated systems.

For optimised external transport and warehousing the Lean dolly can be used together with the Lean adaptor pallet.

Benefits

- Improve work flow
- Reduce handling costs
- Enable reduction of stock level
- Reduce need for floor space
- Improve ergonomics
- Fast and safe truck loading
- Optimize vehicle fill





Lean Pallet Size Dolly

Lean Dolly

External dimensions1200 x 800 x 275 (1017) mm

Tare weight 55-75 kg

Wheel size 160 mm wheels

Wheel type..... 2 fixed & 2 swivel

..... 4 swivel

..... 2 fixed & 4 swivel

Wheel material PU

Working capacity 1000 kg

K.Hartwall wheels are equipped with high quality ball bearings and hub caps for high performance and wheel protection.

Surface treatment: Blue zinc plated acc. to EN-ISO2081

Safe stacking up to 6 pieces 1680 mm
(With towing arm 2,4 m)


Can be towed with all other towable Lean Dolly units




Also available in ISO- and US-dimensions:

- 1200 x 1000 mm
- 48° x 45°

Standard wheels



Fixed polyurethane wheel



Swivel polyurethane wheel

Designed to carry SLC's, pallets and boxes:

- Pallet sizes: Euro, ISO & 48° x 45°
- SLC's in Euro, ISO or inch sizes
- Cages and foldable boxes

Accessories

- Integrated strapping device
- ESD drag cable
- Total brake on 1 or 2 swivel wheels
- RFID compatibility
- Corner supports

6 wheel option for 360° spinning:

